

AMENDMENTS TO THE CLAIMS

This listing of claims is to replace all prior versions of the claims in the application:

Listing of Claims

1. (Currently Amended) A process for the trenchless installation of an underground product pipe from a first location to a second location at a predetermined depth, comprising:

digging a first access shaft at the first location and a target access shaft at the second location to the predetermined [~~depths;~~] depth;

installing a pipe displacement machine in the first access shaft;

jacking a steerable pilot tube and additional pilot tube sections into the ground from the first access shaft to the target shaft displacing the soil to form a pilot pipe from the first access shaft to the target shaft;

installing a drill string to replace the pilot pipe;

attaching a back reamer of a first diameter to the drill string at the target shaft;

pulling the back reamer from the target shaft to the first access shaft;

and pulling a product pipe into place in the line of the pilot [~~pine~~] pipe .

2. (canceled)

3. (previously presented) The process of claim 1, wherein the drill string is installed utilizing a horizontal directional drilling machine.

4. (original) The process of claim 3, wherein the horizontal directional drilling machine is positioned from the first access shaft a distance of at least about 15 feet with at least 5 feet of distance for each foot that the pilot pipe is below the surface.

5. (original) The process of claim 3, wherein the back reamer is pulled through the bore formed by the drill string by reverse pulling of the horizontal directional drilling machine.

6. (previously presented) The process of claim 1, wherein the product pipe is a continuous length of pipe.

7. (currently amended) The process of claim 1, wherein the drill string is installed from above ground utilizing a horizontal directional drilling machine.

8. (currently amended) The process of claim [1,] 3, wherein the horizontal directional drilling machine is positioned from the first access shaft a distance of at least 15 feet with at least 5 feet of distance for each foot that the pilot pipe is below the surface.

9. (currently amended) The process of claim [1,] 3, wherein the back reamer is pulled through the bore formed by the drill string by reverse pulling of the horizontal directional drilling machine.

10. (previously presented) The process of claim 1, wherein the product pipe is pulled into the line of the pilot pipe from the target access shaft to the first access shaft.

11. (previously presented) The process of claim 1, wherein the product pipe is pulled into the line of the pilot pipe from the first access shaft to the target access shaft.